RM125

1U Compact Server Chassis

Specification

M/B Form Factor	• ATX (12" x 9.6")
Dimension (D×W×H)	• 393 mm × 435 mm × 43.5 mm • 15.5" × 17.1" × 1.7"
Drive Bay	• Internal : 3.5" x 2
	• Slim ODD : 1
PSU	• Form Factor : Flex ATX, Single • Watt : 400 W
Indicator	• 1 x Power Status LED, 1 x HDD Activity LED, 2 x LAN Activity LEDs
Front Control	• Power ON/OFF, System Reset, 2 x USB 2.0 Ports
System Security	• N/A
Cooling Fan	• Front : N/A • Middle : 1 x 97 mm blower, or optional 2 x 40 mm (Up to T=48 mm) middle fans • Rear : N/A
Slot Opening	• 1
Metal Thickness	• 1.0 mm
Net Weight (Chassis only)	• 3.4 Kg
Gross Weight (w/Packing)	• 4.66 Kg
Backplane	• N/A
Rear Window	• Standard
Front Bezel	• N/A
Cubic Feet	• 1.49
Container Info. (Single Packing)	• 20' : 704 • 40' : 1424 • 40'H : 1625

Optional 1 x front 97 mm blower

Optional 2 x front 40 mm fans

Slim ODD or 2.5" HDD with SK51102

Easy-assembly cable wire

Up to 400 W PSU

Easy-assembly LED board

Features & Benefits

- Powerful 1U UP computing
- Fully utilized HDD capacity with Chenbro storage kits
- Outstanding thermal solution

Inside View

Rear View

Front View